



	PRODUCT	TOTAL MAT WEIGHT	OVERALL HEIGHT	DIRT ABSORPTION	MOISTURE ABSORPTION	FIRE CERTIFICATE	SLIP RESISTANCE	SIZE OPTIONS	WASHABLE
OUTDOOR MATS	Logo Outdoor	3.60 kg/sqm	approx. 8 mm	•	•	EN 13501-1 / Bfl-s1	•	Standard widths: 50 cm, 85 cm, 115 cm, 150 cm and 200 cm Standard lengths: all lengths up to 400 cm Bespoke lengths: up to 700 cm	NO
	Water-Horse	3.20 kg/sqm	approx. 7 mm	1000 g/sqm	4 - 5 l/sqm	EN 13501-1 / Eff-s1	NFSI High-Traction	Standard sizes: 60 x 90 cm, 85 x 120 cm, 85 x 150 cm, 115 x 175 cm and 115 x 240 cm	NO
	Concourse Tile	14.1 kg/sqm (12 mm) 22.8 kg/sqm (18 mm)	12 mm or 18 mm	•	•	BS 6307:1982 BS 4790:1987	TM 144:2011	Module size: 50 x 100 cm Module system allows for unlimited size options	NO
	Kleen-Scrape	4.20 kg/sqm	approx. 5.5 mm	•	•	EN 13501-1 / Eff-s1	NFSI High-Traction	Standard sizes: Ribbed: 75 x 85 cm, 85 x 150 cm, 85 x 300 cm Chequerboard: 115 x 175 cm	YES
IN BETWEEN MATS	Matrix Tile	11.6 kg/sqm (12 mm) 20.0 kg/sqm (18 mm)	12 mm or 18 mm	•	•	BS 6307:1982 BS 4790:1987	TM 144:2011	Module size: 50 x 100 cm Module system allows for unlimited size options	NO
	Iron-Horse XL	2.54 kg/sqm	approx. 13 - 14 mm	1000 g/sqm	4 - 5 l/sqm	EN 13501-1 / Cfl-s1	NFSI High-Traction	Standard widths: 85 cm, 115 cm and 150 cm Standard lengths: all lengths up to 400 cm Bespoke lengths: up to 700 cm	YES
	Wash-Horse	2.75 kg/sqm	approx. 13 - 14 mm	800 g/sqm	5 - 6 l/sqm	EN 13501-1 / Dfl-s1	NFSI High-Traction	Standard widths: 85 cm, 115 cm and 150 cm Standard lengths: all lengths up to 400 cm Bespoke lengths: up to 700 cm	YES
INDOOR MATS	Iron-Horse	2.40 kg/sqm	approx. 11 - 12 mm	800 g/sqm	3 - 4 l/sqm	EN 13501-1 / Cfl-s1	NFSI High-Traction	Standard widths: 85 cm, 115 cm and 150 cm. Black Pearl, Black Steel, Black Cedar, Granite and Midnight Grey up to 200 cm Standard lengths: all lengths up to 400 cm Bespoke lengths: up to 700 cm	YES
	Monotone	2.40 kg/sqm	approx. 11 - 12 mm	800 g/sqm	3 - 4 l/sqm	EN 13501-1 / Cfl-s1	NFSI High-Traction	Standard widths: 85 cm, 115 cm and 150 cm Standard lengths: all lengths up to 400 cm Bespoke lengths: up to 700 cm	YES
	Jet-Print	2.48 kg/sqm	approx. 9 mm	600 g/sqm	3 - 4 l/sqm	EN 13501-1 / Cfl-s1	NFSI High-Traction	Standard widths: 60 cm, 75 cm, 85 cm, 115 cm, 150 cm and 200 cm Standard lengths: all lengths up to 400 cm Bespoke lengths: up to 700 cm	YES
	Jet-Print Vision Plus	2.70 kg/sqm	approx. 10 mm	400 g/sqm	3 - 4 l/sqm	EN 13501-1 / Cfl-s1	•	Standard widths: 60 cm, 75 cm, 85 cm, 115 cm, 150 cm and 200 cm Standard lengths: all lengths up to 400 cm Bespoke lengths: up to 700 cm	YES
SPECIAL MATS	Kleen-Komfort Safety	approx. 7.18 kg/sqm	approx. 15 mm	•	•	DOC-FF-1-70	NFSI High-Traction	Standard sizes: 60 x 85 cm, 85 x 150 cm and 85 x 285 cm	YES*
	Kleen-Thru Plus	approx. 4.33 kg/sqm	approx. 8 mm	•	•	EN 13501-1 / Eff-s1	NFSI High-Traction	Standard sizes: 60 x 86 cm and 86 x 143 cm	YES
	Kleen-Komfort Soft	approx. 5.79 kg/sqm	approx. 21 mm	•	•	EN 13501-1 / Cfl-s1	NFSI High-Traction	Standard sizes: 55 x 78 cm, 85 x 150 cm and 85 x 285 cm	YES**
	Kleen-Sticky Mat	•	•	•	•	•	•	Standard sizes: 90 x 45 cm, 90 x 60 cm, 115 x 45 cm, 115 x 60 cm and 115 x 90 cm	NO
	High Visibility Mat	2.48 kg/sqm	approx. 9 mm	600 g/sqm	3 - 4 l/sqm	EN 13501-1 / Cfl-s1	NFSI High-Traction	Standard widths: 60 cm, 75 cm, 85 cm, 115 cm, 150 cm and 200 cm Standard lengths: all lengths up to 400 cm Bespoke lengths: up to 700 cm	YES
	Kable-Mat	approx. 3.95 kg/sqm	approx. 13 mm	800 g/sqm	3 - 4 l/sqm	EN 13501-1 / Dfl-s1	•	Standard sizes: 40 x 120 cm	NO
	Kleen-Tile	approx. 4.20 kg/sqm	approx. 10 mm	•	•	•	•	Tile size: 30.4 x 30.4 cm Interlocking tile system allows for unlimited size options Edging size: 10 mm x 30 cm Edging corner size: 10 mm	NO

* Please note: The size 85 x 285 cm is not launderable - please use vacuum cleaner, brush or high pressure cleaner ** Please note: The size 85 x 285 cm is not launderable - please use vacuum or steam cleaner




Kleen-Tex Industries GmbH
Fürhölzl 2 • A-6341 Ebbs / Kufstein
Austria
T: +43 5372 61380
F: +43 53 72 61 380 49
E: info@kleen-tex.eu
W: www.kleen-tex.eu

Kleen-Tex Polska Sp. z o.o
ul. Fabryczna 5/12 • 26-130 Suchedniów
Polska
T: +48 41 267 25 00
F: +48 41 267 25 01
E: info@kleen-tex.pl
W: www.kleen-tex.pl

Kleen-Tex Industries Limited
Emlyn Street • Bolton • Lancashire
BL4 7EB • United Kingdom
T: +44 (0)1204 7050 70
F: +44 (0)1204 861 016
E: info@kleen-tex.co.uk
W: www.kleen-tex.co.uk

KT-0237-1219 • Subject to technical modifications.



Professional Matting Solutions for Light Industry by Kleen-Tex

