V001.1



DESIGN GUIDELINES Logo Outdoor

Colours are subject to commercial tolerance | Please note we are printing on fabric not on plain paper

www.kleen-tex.eu

V001.1

Artwork Specification

- File types: JPEG, TIFF, BMP, PSD or PNG
- Vector graphics: EPS, CDR, AI or PDF
- Design artwork should be set up at actual size at a 1:1 scale


Colour Selection


Please ensure colours in design conform to one of the following:

- Kleen-Tex Standard Colours
- Pantone Formula Guide (Coated/Uncoated)
- RAL Classic
- HKS

Minimum Text Size

Coloured letters







Sans-Serif Fonts



White letters on a dark background





Sans-Serif Fonts

Scripts & Serif Fonts

Minimum Line Thickness



All line thicknesses must be kept above a minimum of 9 mm or more.

Dark Backgrounds

All line thicknesses must be kept above a minimum of 10 mm or more.

Colour Contrast

Blues & Grays

	629	630	631	632	654	665	666
613	good	good	poor	poor	good	good	good
	contrast						
614	poor	poor	good	good	poor	poor	poor
	contrast						
615	good	poor	poor	good	poor	good	poor
	contrast						
624	poor	poor	good	good	poor	poor	poor
	contrast						
637	good	poor	poor	good	poor	good	poor
	contrast						





Green & Grays

	629	630	631	632	654	665	666
617	good	poor	poor	poor	poor	good	good
	contrast						
618	poor	good	good	good	good	poor	poor
	contrast						
619	good	poor	poor	poor	poor	good	good
	contrast						
620	good	poor	poor	good	poor	good	poor
	contrast						
640	good	poor	poor	poor	poor	good	good
	contrast						
621	good	poor	poor	good	poor	good	poor
	contrast						

Similar Colour Combinations, for example:

	602	603		646	650	660	664
		poor contrast		poor contrast	poor contrast	poor contrast	poor contrast
	604	606	607	639	645	652	661
605	poor contrast						
	615	617	619	637	640	641	655
620	poor contrast						

Please Note

• Thoroughly check contrasts with colour swatches before placing your order.

DESIGN GUIDELINES

V001.1

Points to Consider

Please Do...

	↓ 50 mm	
↔ 50 mm	Keep important elements (such as logos) at least 50 mm from the edge of the mat	↔ 50 mm
	↓50 mm	

Please Do Not Use...




Watermarked Stock Images We will not be able to create designs from artwork with watermarked images. Failure to adhere will result in rejected artwork.



Complex Patterns



Weak Colour Combinations



Script or Condensed Fonts