



<b>Product:</b>	Super-Mat
<b>Customs tariff number:</b>	57032098
<b>Product details:</b>	<ul style="list-style-type: none"> <li>» Dual performance - scrape and wipe</li> <li>» Skid resistant rubber back</li> <li>» PVC-free</li> <li>» Light- and colour resistant</li> <li>» Antistatic</li> <li>» 5 years Manufacturers Guarantee*</li> <li>» 11 years warranty against significant colour loss</li> <li>» Made in Europe</li> </ul>
<b>Burning behaviour:</b>	EN 13501-1 / Dfl-s1
<b>Static electrical propensity:</b>	EN 14041 Antistatic
<b>Slip resistance:</b>	NFSI High-Traction
<b>Total mat weight:</b>	3.10 kg/sqm
<b>Overall height:</b>	approx. 9 - 10 mm
<b>Dirt absorption:</b>	900 g/sqm
<b>Moisture absorption:</b>	3 - 4 l/sqm
<b>Application areas:</b>	<ul style="list-style-type: none"> <li>» Heavy traffic areas</li> <li>» Busy entrances</li> </ul>

<b>Standard widths with borders:</b>	85 cm, 115 cm and 150 cm
<b>Standard widths without borders:</b>	3 cm smaller than for mats with borders (e.g. 82 cm)
<b>Standard lengths:</b>	all lengths up to 400 cm
<b>Bespoke lengths:</b>	up to 700 cm
<b>Colouration:</b>	Solution dyed
<b>Pile:</b>	100 % High-Twist Nylon (HTN) Polyamide 6 with Monofilament
<b>Pile height:</b>	approx. 8 - 9 mm
<b>Pile weight:</b>	without substrate: 695 g/sqm with substrate: 940 g/sqm
<b>Backing:</b>	100 % Nitrile rubber Available with kleeled or smooth backing
<b>Rubber thickness:</b>	1.80 mm
<b>Rubber weight:</b>	2.20 kg/sqm
<b>Border width:</b>	20 mm
	Available with or without borders
<b>Border thickness:</b>	2.80 mm
<b>Cleaning:</b>	<ul style="list-style-type: none"> <li>» Washable up to 60 °C</li> <li>» Tumble dry up to 60 °C</li> </ul>

### Colours:

