

---

## CLASSIFICATION OF REACTION TO FIRE ACCORDANCE WITH EN 13501-1:2018

---

### 1. Introduction

This classification report defines the classification assigned to **floor mat „Kleen-Komfort Office”** in accordance with the procedures in EN 13501-1:2018.

**Sponsor:** Kleen -Tex Polska Sp. z o.o.  
Fabryczna 5/12  
26-130 Suchedniów, Poland

**Prepared by:** SYCHTA LABORATORIUM Sp. J.  
Laboratorium Badań Palności Materiałów  
ul. Ofiar Stutthofu 90  
72-010 Police, Poland

**Notified Body No:** -

**Product name:** Floor mat „Kleen-Komfort Office”

**Classification report No:** SL/Z-325/EN13501/0342a/2022 - draft

**Date of issue:** 30.05.2022

This classification report consists of four pages and may only be used or reproduced in its entirety.

### 2. Details of classified product

#### 2.1. General

The product, **floor mat „Kleen-Komfort Office”**

## 2.2. Product description

The product, **floor mat „Kleen-Komfort Office”**, is described below or is described in the reports provided in support of classification listed in 3.1

**Pile:** 50 % Polyester 50 % Polypropylene. Pile height: approx. 4 mm. Pile weight: 750 g/m<sup>2</sup>. **Backing:** 100% Nitrile rubber. Rubber thickness: 1.80 mm. Rubber weight 2,09 kg/m<sup>2</sup>. **Foam:** 100% Nitrile foam. Foam thickness: 11,5 mm. Foam weight approx. 3,00 kg/m<sup>2</sup>. **Total mat weight: approx. 5,89 kg/m<sup>2</sup>. Overall height: approx. 18 mm.**

## 3. Reports and results in support of this classification

### 3.1. Specific conditions

-

### 3.2. Reports

Name of Laboratory	Name of sponsor	Report ref. No.	Test method and date Field of application rules and date
Sychta Laboratorium	Kleen -Tex Polska Sp. z o.o.	SL/Z-325/EN11925/0341a/2022	PN-EN ISO 11925-2 26.05.2022 r.

### 3.3. Results

Test method and test number	Parameter	No. Tests <sup>a</sup>	Results	
			Continuous parameter - mean (m)	Compliance with parameters
PN-EN ISO 11925-2 Exposure time 30 s	Flame spread > 150 mm in 20 s, mm	12	(-)	Compliant
	Ignition of paper		(-)	Compliant

<sup>a</sup> Not for extended application, (-): not applicable

## 4. Classification and field of application

### 4.1. Reference of classification

This classification has been carried out in accordance with EN 13501-1:2018.

### 4.2. Classification

The product, **floor mat „Kleen-Komfort Office”**, in relations to its reaction to fire behaviour is classified:

**E**

~~The additional classification in relations to smoke production is:~~

-

~~The additional classification in relations to flaming droplets / particles is:~~

-

The format of the reaction to fire classification for construction products excluding floorings and linear pipe thermal insulation products is:

Fire behaviour		Smoke production			Flaming droplets	
<b>E</b>	-	<b>s</b>	-	,	<b>d</b>	-

**Reaction to fire classification: E**

### 4.3. Field of application

This classification is valid for the following product parameters:

- floor mat - rigid surface, patterned carpet (melange), with foam and rubber backing, black colour
- total thickness of 15,6-15,9 mm
- weight per unit area 6,4 kg/m<sup>2</sup>

The classification is valid for the following end use applications:

-

### 5. Limitations

This classification document does not represent type approval or certification of the product.

*Signature of person  
undertaking classification:*

*dr inż. Krzysztof Sychta*

*Signature of person  
authorising report:*