

















Interlocking area tiles designed for wet areas

The curved design of the lines and hollow construction promotes immediate drainage and allows water to pass directly through the tile. The soft surface of provides a comfortable, slip resistant, safe and dry cushioned surface for bare feet. Easy to install and keep clean.

Why Choose Kleen-Tile?

- » Interlocking wet area tile
- » UV resistant material
- » Reduce wet area accidents
- » Soft touch traction for bare feet
- » Modular construction suitable for any area
- » Easy to install
- » 3 year or 3 million crossings quarantee
- » Made in Europe

Technical Details

Materials

» UV-resistant, anti bacterially treated vinyl

Applications

- » Poolside
- » Wet rooms
- » Locker rooms » Shower rooms

Certifications

- » EN 13501-1 / Bfl-s1 » EN ISO 11925-2
- » EN ISO 9239-1
- » DIN 51097: A + B + C
- » DIN EN 13451/15288-1: 26°
- » ISO 16000-9: TVOC Class A+

Specification

Heiaht

Weight

» Approx. 10 mm » Approx. 4.2 kg/m²

Tile Size

» 30.4 x 30.4 cm

Interlocking modular link system allows for infinite size option

Pack Size

» 16 tiles per pack (=1.47 m²)

Full Technical Data



Pastel Blue

Grev

Dark Blue

For all mats we reseve the right of production-related tolerance of +/- 3% in size. Colours are subject to commercial tolerance.



T: +43 53 72 61 3 80

E: info@kleen-tex.eu

