



## Interlocking area tiles designed for wet areas

The curved design of the lines and hollow construction promotes immediate drainage and allows water to pass directly through the tile. The soft surface of provides a comfortable, slip resistant, safe and dry cushioned surface for bare feet. Easy to install and keep clean.

Why Choose Kleen-Tile?	Technical Details	Specification
» Interlocking wet area tile	Materials » UV-resistant, anti bacterially treated vinyl	Height Weight » Approx. 10 mm » Approx. 4.2 kg/m <sup>2</sup>
» UV resistant material	Applications	Tile Size
» Reduce wet area accidents	» Poolside » Wet rooms » Locker rooms » Shower rooms	» 30.4 x 30.4 cm
» Soft touch traction for bare feet	Certifications	Interlocking modular link system allows for infinite size option
» Modular construction - suitable for any area	» EN 13501-1 / Bfl-s1 » EN ISO 11925-2	Pack Size
» Easy to install	» EN ISO 9239-1 » DIN 51097: A + B + C	» 16 tiles per pack (=1.47 m²)
» 3 year or 3 million crossings guarantee	» DIN EN 13451/15288-1: 26° » ISO 16000-9: TVOC Class A+	
» Made in Europe		Full Technical Data

Dark Blue

Pastel Blue

Grey



For all mats we reseve the right of production-related tolerance of +/- 3% in size. Colours are subject to commercial tolerance.

For more information, please contact our Customer Service Team: T: +44 (0)1204 70 50 70 E: info@kleen-tex.co.uk

