Kleen-Tex

Kleen-Cable Mat EV

Technical Datasheet



$ \mathscr{T} = \bigotimes \mathscr{Q} \stackrel{\overset{\sim}{\simeq}}{=} \widehat{\mathscr{P}} \stackrel{\overset{\sim}{\otimes}}{=} \widehat{\mathscr{P}} \stackrel{\overset{\circ}{\otimes}}{=} \widehat{\mathscr{P}} \stackrel{\overset{\circ}{\otimes}{=} \widehat{\mathscr{P}} \stackrel{\overset{\circ}{\otimes}}{=} \widehat{\mathscr{P}} \stackrel{\overset{\circ}{\otimes}{=} \widehat{\mathscr{P}} \stackrel{\overset{\circ}{\otimes}}{=} \widehat{\mathscr{P}} \stackrel{\overset}{\otimes}{\cong}{=} \widehat{\mathscr{P}} \stackrel{\overset}{\otimes}{\cong} \stackrel{\overset}$			
Product:	Kleen-Cable Mat EV	Backing:	100% Nitrile Rubber (15% recycled nitrile rubber)
Category:	Transportation	Backing Weight:	5.8kg/sqm
Sub-Category:	Car Mats	Backing Height:	4.8mm
		Border Width:	30mm
Typical Applications:	EV Charging Points	Border Thickness:	4.8mm
	Garages		
	Driveways	Static Propensity:	EN14041 Antistatic
	Forecourts	Colourfast & Lightfast:	Yes
		Underfloor Heating:	Yes
Total Product Height:	~4.8mm		
Total Product Weight:	~5.8kg/sqm		
Standard Size	40 x 120cm		
	40 x 160cm		
	40 x 200cm		
Customs Tariff Number:	40169100		
Origin	Made In Europe		





For all mats, we reserve the right of a production-related tolerance of +/- 3% in size. Colours are subject to commercial tolerance.

06/02/2025