



<b>Product:</b>	<b>Kleen-Fit Guard DC008</b>	<b>Grid Material:</b>	Aluminium – Minimum 95% recycled content in clo
<b>Category:</b>	Fitted Entrance System	<b>Grid Recycled Content:</b>	95% recycled content
<b>Sub-Category:</b>	Grid System	<b>Anodised Grid Lengths</b>	
<b>Typical Applications:</b>	Extremely high traffic areas such as train stations and airports	Black:	Max. 4000mm
<b>Max Module Length:</b>	4000mm Panels are manufactured specifically to customer requirements. Panel lengths available up to 4000mm left to right as required (Anodised panel lengths vary – see below)	Light Gold:	Max. 2600mm
<b>Installation Method</b>	Recessed in matwell or surface-laid with ramp frame	Medium Gold:	Max. 2600mm
<b>Insert Material:</b>	Flecked rubber infills	Dark Gold:	Max. 2600mm
<b>Insert Depth:</b>	12mm 17mm	Gun Metal Grey:	Max. 2500mm
<b>Origin</b>	Made In Europe	Light Bronze:	Max. 1600mm
		Medium Bronze:	Max. 4000mm
		Dark Bronze:	Max. 4000mm
		<b>Fire Rating:</b>	Hot Metal Nut BS4790:1987 (1996) - Low DIN 4106 – B2
		<b>ISO9001:2018:</b>	Yes
		<b>BS8300 DDA Compliant:</b>	Yes
		<b>BS4790:1987:</b>	Yes
		<b>R9 in accordance with BGR 181:</b>	Yes
		<b>Slip Resistancy:</b>	Slip resistance classification R9 in accordance with BGR 181, Classification C in wet areas in accordance with DIN51097 (the classification for wet areas runs from A to C with C being the best, which guarantees a high level of anti-slip properties) Dynamic coefficient of friction > 0.3μ in accordance with EN 13893



Black

Blue

Grey