



Product:	Kleen-Fit System Brush	Insert Material:	100% looped polyamide fibers
Category:	Fitted Entrance System	Manufacturing Process:	Felting
Sub-Category:	Grid System	Pile Weight:	1.5kg/m ² ±10%
		Pile Height:	4.5mm ±10%
Typical Applications:	Shopping Centres Leisure Facilities Public Buildings Hospitals Offices	Frame Material:	Aluminium with Stainless Steel wire
		Aluminium Profile:	EN AW 6063 T6
		Certification	
Maximum Length:	Bespoke manufacturing - No maximum	Hygiene Certificate:	B-BK-60211-0449/19
Maximum Width:	Bespoke manufacturing - No maximum	Anti-Slip Rating:	DIN 51130:2014 - R11
Height Options:	Low profile - 12mm Medium profile - 17mm High profile - 22mm	Flame Retardancy:	EN13501-1 / Cf-s1
		Declaration of Performance:	CE
Total Weight:	12mm - 10.13kg/m ² ±10% 17mm - 10.69kg/m ² ±10% 22mm - 11.62kg/m ² ±10%	Stationary Load:	2500kg/m ²
		Antistatic Rating:	ISO 6356
Total Thickness:	10mm ±10%	Environmental System:	ISO14001:2015
Profile Width:	30mm		
Profile Spacing:	3 - 4.5mm		
Origin:	Made In Europe		



Black

Brown

Grey

For all mats, we reserve the right of a production-related tolerance of +/- 3% in size. Colours are subject to commercial tolerance.