



<b>Product:</b>	<b>Kleen-Thru Plus</b>	<b>Rubber:</b>	100% Nitrile Rubber
<b>Category:</b>	Anti-Fatigue Mats	<b>Rubber Weight:</b>	kg/sqm
<b>Sub-Category:</b>	Industrial	<b>Rubber Thickness:</b>	mm
<b>Typical Applications:</b>	Professional Kitchens Wet Areas Workstations Bars	<b>Antibacterial Test:</b>	AATCC 30 / AATCC 100
<b>Total Product Height:</b>	8mm	<b>Flame Retardancy:</b>	EN 13501-1 / Efl-s1
<b>Total Product Weight:</b>	4.33kg/sqm	<b>Static Propensity:</b>	-
<b>Standard Sizes</b>	60 x 86cm 86 x 143cm	<b>Lightfast &amp; Colourfast:</b>	Yes
<b>Customs Tariff Number:</b>	40169100	<b>Underfloor Heating:</b>	Yes
<b>Origin</b>	Made In Europe	<b>Accessories:</b>	Mat Connector for secure linking of multiple mats
		<b>Resistance to Fungi:</b>	ASTM G21-2015
		<b>Antibacterial Element:</b>	ISO 22196

**Notes:**

NAMSA (North American Science Associates) has indicated that Kleen-Thru Plus is rated 0/NZ (no growth, no zone) in the AATCC TM 30, Part 111 test, meaning this mat has an effective fungi static treatment that helps control the bacterial and fungal growth that cause odour in the mat.

The anti-microbial treatment is registered in the USA by the Environmental Protection Agency and is bound and non-migrating, which means it is present for the life of the mat and will not wash off or rub off even when subjected to prolonged industrial washing. This treatment only protects the Kleen-Thru Plus mat and not the people who are using it. Always clean this product properly after each use.



For all mats, we reserve the right of a production-related tolerance of +/- 3% in size. Colours are subject to commercial tolerance.  
\*85x285cm is not launderable. Please use vacuum, brush or high pressure water clean.

\* 2 years under industrial laundry conditions