# Iron-Horse Absorb

**Technical Datasheet**

| | |
|---|---|
| **Product:** | **Iron-Horse Absorb** |
| **Category:** | Standard Mats |
| **Sub-Category:** | Entrance |
| **Typical Applications:** | Entrances<br>Corridors<br>Receptions<br>Elevators |
| **Total Product Height:** | ~ 15mm |
| **Total Product Weight:** | 2.85kg/sqm |
| **Standard Widths:** | 85cm<br>115cm<br>150cm<br>200cm |
| **Standard Widths without Borders:** | 80cm<br>110cm<br>145cm<br>195cm |
| **Maximum Lengths:** | 700cm |
| **Customs Tariff Number:** | 57032999 |
| **Origin** | Made In Europe |

| | |
|---|---|
| **Colouration:** | Solution Dyed |
| **Pile Material:** | A combination of Micro Nylon and High-Twist Nylon (HTN) Polyamide 50% recycled yarn |
| **Pile Weight:** | 2g/sqm |
| **Pile Height:** | ~ 14mm |
| **Backing Material:** | 100% Phthalate-free Nitrile Rubber |
| **Backing Weight:** | 1.75kg/sqm |
| **Backing Height:** | 1.5mm |
| **Backing Finish:** | Kleeted or Flat |
| **Border Width:** | 20mm |
| **Border Thickness:** | 2.5mm |
| **Dirt Absorption:** | 2kg/sqm |
| **Moisture Absorption:** | 5 - 6l/sqm |
| **Flame Retardancy:** | EN13501-1 / Cfl-s1 |
| **Static Propensity:** | EN14041 Antistatic |
| **Lightfast & Colourfast:** | Yes |
| **Underfloor Heating:** | Yes |



**Mineral Grey**

For all mats, we reserve the right of a production-related tolerance of +/- 3% in size. Colours are subject to commercial tolerance.

*2 year guarantee under industrial laundry conditions