

Kleen-Thru Plus

Technical Datasheet



Product:	Kleen-Thru Plus		Rubber:	100% Nitrile Rubber
Category:	Anti-Fatigue Mats		Rubber Weight:	kg/sqm
Sub-Category:	Industrial		Rubber Thickness:	mm
Typical Applications:	Professional Kitchens		Antibacterial Test:	AATCC 30 / AATCC 100
	Wet Areas		Flame Retardancy:	EN 13501-1 / Efl-s1
	Workstations		Static Propensity:	-
	Bars		Lightfast & Colourfast:	Yes
Total Product Height:	8mm		Underfloor Heating:	Yes
			Accessories:	Mat Connector for secure linking of multiple mats
Standard Sizes and Weight:	60 x 86 cm	2.00 kg/mat	Resistance to Fungi:	ASTM G21-2015
	86 x 143cm	5.23 kg/mat	Antibacterial Element:	ISO 22196
Customs Tariff Number:	40169100			
Origin	Made In Europe			

Notes:

NAMSA (North American Science Associates) has indicated that Kleen-Thru Plus is rated 0/NZ (no growth, no zone) in the AATCC TM 30, Part 111 test, meaning this mat has an effective fungi static treatment that helps control the bacterial and fungal growth that cause odour in the mat.

The anti-microbial treatment is registered in the USA by the Environmental Protection Agency and is bound and non-migrating, which means it is present for the life of the mat and will not wash off or rub off even when subjected to prolonged industrial washing. This treatment only protects the Kleen-Thru Plus mat and not the people who are using it. Always clean this product properly after each use.

