Super-Mat

Technical Datasheet

Product:	**Super-Mat**	**Colouration:**	Solution Dyed
Category:	Standard Mats	**Pile Material:**	100% Econyl® regenerated nylon
Sub-Category:	Eco	**Pile Weight:**	900g/sqm
		Pile Height:	~ 9mm
Typical Applications:	Entrances		
	Corridors	**Backing Material:**	100% Phthalate-free Nitrile Rubber
	Receptions	**Backing Weight:**	2.2kg/sqm
	Elevators	**Backing Height:**	1.8mm
		Backing Finish:	Kleeted or Flat
Total Product Height:	~ 10mm		
Total Product Weight:	3.1kg/sqm	**Border Width:**	20mm
		Border Thickness:	2.8mm
Standard Widths:	85cm		
	115cm	**Dirt Absorption:**	950g/sqm
	150cm	**Moisture Absorption:**	3 - 4l/sqm
Standard Widths without Borders:	80cm	**Slip Resistance:**	NFSI High-Traction
	110cm	**Flame Retardancy:**	EN13501-1 / Cfl-s1
	145cm	**Static Propensity:**	EN14041 Antistatic
		Lightfast & Colourfast:	Yes
Maximum Lengths:	700cm	**Underfloor Heating:**	Yes
Customs Tariff Number:	57032999		
Origin	Made In Europe		



Black Lava DF 665



Heather Grey DF 740

For all mats, we reserve the right of a production-related tolerance of +/- 3% in size. Colours are subject to commercial tolerance.

*2 year guarantee under industrial laundry conditions

Sedex | Member

06/08/2026