



info.za@kleen-tex.com  
www.kleen-tex.co.za

# Entrance X-Grip



## Standing strong against heavy foot traffic

An extremely hard wearing, durable commercial entrance matting system that facilitates low maintenance costs due to robust composition and multi-directional pile. As an optional extra, a basic name and/or logo can be added.

Why choose Entrance X-Grip?	Technical Details	Specification
<ul style="list-style-type: none"> <li>» Abrasive scraping action</li> <li>» Hard wearing and durable</li> <li>» Low upkeep costs</li> <li>» Fray and unraveling resistant</li> <li>» Sound damping properties</li> <li>» Easy to clean dirt collection channel</li> <li>» Easy to install</li> <li>» Compatible with X-Grip</li> <li>» 2 years manufacturers guarantee*</li> </ul>	<p><b>Materials</b></p> <ul style="list-style-type: none"> <li>» 100% PVC tile with nylon or polypropylene carpet inserts</li> </ul> <p><b>Category</b></p> <ul style="list-style-type: none"> <li>» Fitted Entrance Systems</li> </ul> <p><b>Applications</b></p> <ul style="list-style-type: none"> <li>» Suitable for indoor use</li> <li>» Shopping centres, leisure facilities, public buildings, hospitals, offices</li> </ul> <p><b>Coloration*</b></p> <ul style="list-style-type: none"> <li>» Black PVC tile with solution dyed carpet inserts</li> </ul>	<p><b>Total Height</b></p> <ul style="list-style-type: none"> <li>» ± 14 mm</li> </ul> <p><b>Weight</b></p> <ul style="list-style-type: none"> <li>» ± 8.80kg/m<sup>2</sup></li> </ul> <p><b>Tile Size*</b></p> <ul style="list-style-type: none"> <li>» ± 445 cm (L) x 295 cm (W)</li> </ul> <p><b>Non-Standard Sizes*</b></p> <ul style="list-style-type: none"> <li>» The tiles are clipped together to form any size required</li> </ul>



Blue



Charcoal



Chocolate



Grey



Mali



Turkey

**Kindly Note:**

\* The manufacturers guarantee is subject to recommended product application and care.

\* Colours are subject to commercial tolerance.

\* Mat colours may vary from paper print or electronic device view.

\* For all mats we reserve the right of production-related tolerance of ± 3% in size.

