



Product:	Kleen-Thru Plus	Rubber:	100% Nitrile Rubber
Category:	Anti-Fatigue Mats	Rubber Weight:	kg/sqm
Sub-Category:	Industrial	Rubber Thickness:	mm
Typical Applications:	Professional Kitchens Wet Areas Workstations Bars	Antibacterial Test:	AATCC 30 / AATCC 100
Total Product Height:	8mm	Flame Retardancy:	EN 13501-1 / Efl-s1
Total Product Weight:	4.33kg/sqm	Static Propensity:	-
Standard Sizes	60 x 86cm 86 x 143cm	Lightfast & Colourfast:	Yes
Customs Tarriff Number:	40169100	Underfloor Heating:	Yes
Origin	Made In Europe	Accessories:	Mat Connector for secure linking of multiple mats

Notes:
 NAMSA (North American Science Associates) has indicated that Kleen-Thru Plus is rated 0/NZ (no growth, no zone) in the AATCC TM 30, Part 111 test, meaning this mat has an effective fungi static treatment that helps control the bacterial and fungal growth that cause odour in the mat.
 The anti-microbial treatment is registered in the USA by the Environmental Protection Agency and is bound and non-migrating, which means it is present for the life of the mat and will not wash off or rub off even when subjected to prolonged industrial washing. This treatment only protects the Kleen-Thru Plus mat and not the people who are using it. Always clean this product properly after each use.

